CLAIM AMENDMENTS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

(currently amended) A firearm having a slide, said firearm comprising:
 a removable, non-rotary magazine for accommodating a round of ammunition therein;

a magazine follower disposed within said magazine, said magazine follower supporting said round of ammunition and including a protruding lip extending outwardly therefrom; and

wherein a distal end of said protruding lip extends beyond a plane defined by an outer wall of said magazine <u>and said magazine defines an elongated housing having a rounded face disposed substantially opposite a planar face; and</u>

wherein a mating seam of said magazine is formed in said planar face.

- (original) The firearm according to claim 1, further comprising:

 a biasing member operatively connected to said magazine follower, said biasing
 member urging said distal end of said protruding lip beyond said plane defined by said outer wall of said magazine.
- 3. (canceled)
- 4. (previously presented) The firearm according to claim 1, further comprising: a slide lever having a biasing arm which selectively communicates with said distal end of said protruding lip when said protruding lip extends beyond said outer wall of said magazine.
- 5. (original) The firearm according to claim 4, wherein: said biasing arm includes a non-tapered distal end.

6. (previously presented) The firearm according to claim 4, wherein:

said slide lever includes a restraining catch and selectively pivots between an engaging position in which said restraining catch engages a slide recess in said slide, and a non-engaging position in which said restraining catch does not engage said slide recess; and

said restraining catch pivots to said engaging position when said biasing arm communicates with said protruding lip.

- 7. (previously presented) The firearm according to claim 4, wherein: said slide lever includes a restraining catch; and movement of said slide is arrested when said restraining catch engages a recess in said slide.
- 8. (original) The firearm according to claim 1, further comprising:
 a cutout formed adjacent an upper portion of said magazine;
 a follower body extending downwardly from said magazine follower and into an interior of said magazine; and

wherein said follower body is configured such that said follower body is not disposed opposite said cutout when said magazine follower has been biased adjacent said upper portion of said magazine.

9. (original) The firearm according to claim 4, further comprising:

a magazine spring disposed within said magazine, said magazine spring urging said magazine follower upward in a feeding direction; and

said protruding lip communicates with said biasing arm when said magazine spring has biased said magazine follower adjacent an upper portion of said magazine.

10. (currently amended) A firearm having a slide, said firearm comprising: a removable, non-rotary magazine;

a magazine follower disposed within said magazine, said magazine follower having a protruding lip extending outwardly therefrom;

a biasing member operatively connected to said magazine follower; and wherein a distal end of said protruding lip is urged by said biasing member to extend beyond a plane defined by an outer wall of said magazine and said magazine defines an elongated housing having a rounded face disposed substantially opposite a planar face; and

wherein a mating seam of said magazine is formed in said planar face.

- 11. (original) The firearm according to claim 10, further comprising:
 a cutout formed in an upper portion of said magazine; and
 wherein said distal end extends beyond said plane defined by said outer wall of
 said magazine when said protruding lip is disposed opposite said cutout.
- 12. (cancelled)
- 13. (previously presented) The firearm according to claim 10, further comprising: a slide lever having a biasing arm which selectively communicates with said distal end of said protruding lip when said protruding lip extends beyond said outer wall of said magazine.
- 14. (original) The firearm according to claim 13, wherein: said biasing arm includes a non-tapered distal end.
- 15. (previously presented) The firearm according to claim 13, wherein: said slide lever includes a restraining catch and selectively pivots between an engaging position in which said restraining catch engages a slide recess in said slide, and a non-engaging position in which said restraining catch does not engage said slide recess; and

said restraining catch pivots to said engaging position when said biasing arm communicates with said protruding lip.

- 16. (previously presented) The firearm according to claim 13, wherein: said slide lever includes a restraining catch; and movement of said slide is arrested when said restraining catch engages a recess in said slide.
- 17. (original) The firearm according to claim 10, further comprising:
 a follower body extending downwardly from said magazine follower and into an interior of said magazine; and

wherein said follower body is configured such that said follower body is not disposed opposite said cutout when said magazine follower has been biased adjacent said upper portion of said magazine.

18. (original) The firearm according to claim 13, further comprising:
a magazine spring disposed within said magazine, said magazine spring urging said magazine follower upward in a feeding direction; and

said protruding lip communicates with said biasing arm when said magazine spring has biased said magazine follower adjacent an upper portion of said magazine.

- 19. (previously presented) The firearm according to claim 10, wherein: said distal end of said protruding lip is beveled.
- 20. (cancelled)